

DMR Dispersion Management Reflector




TeraXion's all-fiber PowerSpectrum™ DMR chirped fiber Bragg gratings (CFBG) provide precise compensation for either anomalous or normal dispersion for mode-locked ultrafast lasers. The DMR has especially high dispersion accuracy and is compatible with most mode-locked laser configurations including picosecond and femtosecond lasers, customizable wavelengths, cavity lengths and repetition rates.

Mode-locked ultrafast fiber lasers have replaced most of their solid-state counterparts because of superior ruggedness, easier miniaturization, and simpler integration. TeraXion is a pioneer in designing and manufacturing chirped FBGs for ultrafast fiber lasers. After a decade of refinement, the PowerSpectrum™ DMR is unmatched in the industry for meeting the demanding requirements of femtosecond pulse generation.

Top 5 Features

- **Accurate:** Precision dispersion management enables ultra-short pulse durations by ensuring that the full spectrum of wavelengths maintains a proper phase relation.
- **Robust:** The monolithic design of the all-fiber PowerSpectrum™ DMR intrinsically eliminates misalignment caused by temperature changes or mechanical shock, enabling pulse durations as short as 50 fs.
- **Reliable:** TeraXion's chirped FBG products have been the critical components for a variety of fiber laser systems for over a decade.
- **Standardized:** We stock a range of reflectors designed for PM 980 fiber and optimized for the 1030 nm wavelength band.
- **Adaptable:** PowerSpectrum™ DMR reflectors are available as custom-made components, selectable wavelength, bandwidth, fiber-type, and dispersion parameters.

Mode-locked ultrafast laser with chromatic dispersion management



Standard Configuration Specifications (for femtosecond lasers)


Parameters	Configuration 1	Configuration 2	Units
Reflection bandwidth at -3dB FWHM ⁽¹⁾	20 ± 1	10 ± 1	nm
Peak reflectivity	>12.0	>25.0	%
D ₂ ⁽²⁾	+0.20	+0.42	ps/nm
D ₃ ⁽²⁾	0	0	ps/nm ²
Center wavelength at room temperature ⁽²⁾ (slow axis)	1030 ± 3		nm
Spectral shape	Gaussian		
Wavelength referenced to	Air		
Connector type	None		
Fiber type	PM 980		
Packaging	UV-cured acrylate		
Pigtail length (on each side)	≥1		m
RoHS compliant	Yes		

- (1) Short wavelengths are reflected first
 (2) The group delay function is: $GD = D_1 + D_2(\lambda - \lambda_0) + D_3(\lambda - \lambda_0)^2$
 (3) Room temperature = 20 °C to 23 °C

Customizable Specifications

Parameters	For picosecond laser	For femtosecond laser	Units
Wavelength range (full coverage)	Between 780 and 2200		nm
Bandwidth	0.015 to 2	>2 to 50	nm
Dispersion rate	>10 to 1000	0.015 to 10	ps/nm
Chromatic dispersion management	Up to third order		
Reflectivity	Up to 95	Up to 50 (typ. 20)	%
Fiber type	Single-mode, polarization maintaining or large mode area		
Package	Recoated or loose tube		

Use the chart below when ordering your customized item



Nomenclature options	
1	= Wavelength (nm)
2	= Bandwidth at -3 dB (nm)
3	= Reflectivity (%)
4	= $\pm D_2$ or $\pm \beta_2$ Dxxx (ps/nm) β xxx (ps ²)
5	= $\pm D_3$ or $\pm \beta_3$ xxx (ps/nm ²) xxx (ps ³)
6	= Fiber type P1 = polarization maintaining P2 = PM with cladding suppression mode S1 = Single mode non-PM S2 = CMS non-PM

Ordering information

For orders, questions, specific requirements or to learn more about TeraXion’s products, contact us at info@teraxion.com



teraxion.com
2716 Einstein Street
Quebec, Quebec, CANADA G1P 4S8
+1 (877) 658-8372 / info@teraxion.com

© 2021 TeraXion Inc. All rights reserved.
TeraXion Inc. reserves all of its rights to make additions, modifications, improvements, withdrawals and/or changes to its product lines and/or product characteristics at any time and without prior notice. Although every effort is made to ensure the accuracy of the information provided on this information sheet, TeraXion Inc. does not guarantee its exactness and cannot be held liable for inaccuracies or omissions.