

PowerSpectrum™

DMR-1030-20-12 (+D0.2+0)-P1

Item # ED57617

Optical Parameters

Center Wavelength (λ_0) ⁽¹⁾	Slow Axis	1030	nm
Tolerance on Center Wavelength	+/-	3	nm
Peak Reflectivity	>	12	%
Reflection Bandwidth at -3 dB (FWHM)		20	nm
Tolerance on Reflection Bandwidth	+/-	1	nm
D ₂ ⁽³⁾		0.2	ps/nm
D ₃ ⁽³⁾		0	ps/nm ²
Spectral Shape		Gaussian	
Wavelength Referenced to		Air	

Mechanical Parameters

Pigtail Length (On Each Side)	≥	1	m
Connectors Types		No Connectors	
Proof Test (Final Product)	≥	50	kpsi
Recoat Type		UV Cured Acrylate	

Fiber Parameters

Fiber Type		PM980	
------------	--	-------	--

(1): Room temperature (20-23°C)

(2): Short wavelengths reflected first

(3): The group delay function of the device is: $GD = D_1 + D_2 * (\lambda - \lambda_0) + D_3 * (\lambda - \lambda_0)^2 + D_4 * (\lambda - \lambda_0)^3$

MKT-FSTD-PWS-DMR01 201501-1.0

© 2015 by TeraXion Inc. All rights reserved.

TeraXion Inc. reserves all of its rights to make additions, modifications, improvements, withdrawals and/or changes to its product lines and/or product characteristics at any time and without prior notice. Although every effort is made to ensure the accuracy of the information provided on this spec sheet, TeraXion Inc. does not guarantee its exactness and cannot be held liable for inaccuracies or omissions.

TeraXion

TERAXION.COM