

# PowerSpectrum™

CM-V — Chirped Module with VBG Compressor for Ultrafast Laser

45 ps/nm Configuration : CM- 1030V-400[16F-10.9-(45)]-M1-0P2-0T1

## Overview

The PowerSpectrum™ - Chirped Module for Ultrafast Laser combines TeraXion's Tunable Pulse Stretcher and a VBG compressor. Matched in house, the pair offers 45 ps/nm of stretching factor and the possibility to achieve a compressed pulse duration of < 400 fs. It is the ideal solution for a robust, compact and cost-effective chirped-pulse amplified (CPA) femtosecond laser, no matter the gain medium.

## System Parameters

Center Wavelength	Slow Axis	1030	nm
Minimum recompressed pulse duration <sup>1</sup>	<	400	fs
Beam Quality M2	<	1.35	
Stretching Factor		45	ps/nm
Total Stretching Window <sup>2</sup>		500	ps

1 : Depends on pulse bandwidth


2 : Limited by VBG length

## PWS—Tunable Pulse Stretcher Optical Parameters

Reflectivity	>	70	%
Spectral Bandwidth (FWHM)		16	nm
Tolerance on Spectral Bandwidth	+/-	1	nm
Full D <sub>2</sub> Tuning Range		1.35	ps/nm
Full D <sub>3</sub> Tuning Range		0.006	ps/nm <sup>2</sup>
Fiber Type		PMCMS	
Pigtail length	>	1	m
Connector Type		None	
Module Dimensions (without cable)		14 x 22 x 130	nm
Supply Voltage		5	V
Power Consumption		3	W
Control Protocol		I <sup>2</sup> C	



The PowerSpectrum™—TPSR



i<sup>2</sup>C Software Platform

MKT-FSTD-PWS-CM-V01 2017-11-1.0

**TeraXion**

TERAXION.COM

# PowerSpectrum™

CM-V — Chirped Module with VBG Compressor for Ultrafast Laser  
45 ps/nm Configuration : CM- 1030V-400[16F-10.9-(45)]-M1-0P2-0T1

## OptiGrate—Volume Bragg Grating Parameters

Spectral Bandwidth		10.85	nm
Tolerance on Spectral Bandwidth	+/-	1.1	nm
Diffraction Efficiency	>	85	%
Grating Thickness		50	mm
Tolerance on Grating Thickness	+/-	5	mm
Grating Aperture (clear aperture > 85%)		5 x 5	mm
Assembly Dimensions		55 x 6 x 10	mm
AR Coating Type	High Energy Broadband		

## Power and Communication Module (Optional)

Supply Voltage	5	V
Power Consumption	3	W
Control Interface	USB to I <sup>2</sup> C	
CableType (included)	DB15 to Hirose	
Module Dimensions (without cable)	55 x 80 x 150	mm



Power and Communication Module

## 3-Port Optical Circulator (Optional)

Center Wavelength		1030	nm
Insertion Loss (Maximum)	<	3.6	dB/port
Isolation	>	20	dB
Fiber Type		PM980	
Optical Power Handling		50	mW

## Ordering information

For orders, questions, specific requirements or to learn more about TeraXion's products, contact us at

[info@teraxion.com](mailto:info@teraxion.com)

© 2017 by TeraXion Inc. All rights reserved.

TeraXion Inc. reserves all of its rights to make additions, modifications, improvements, withdrawals and/or changes to its product lines and/or product characteristics at any time and without prior notice. Although every effort is made to ensure the accuracy of the information provided on this spec sheet, TeraXion Inc. does not guarantee its exactness and cannot be held liable for inaccuracies or omissions.

**TeraXion**

TERAXION.COM